



## CAPACITOR SUBSTITUTION BOXES

- Cat: EM0930-001 3 dial x 0.001uF 400V
- Cat: EM0931-001 3 dial x 0.01uF 400V
- Cat: EM0932-001 4 dial x 0.001uF 400V

### EM0932-001 4 dial x 0.001uF box



**Physical size:** 4 dial: 240x75x80mm LxWxH      **Weight:** 0.55 kg

**DESCRIPTION:** Accuracy: +/- 5% at any setting.

Capacitance box, providing decades of capacitance.

**EM0930-001** 3 dial **Total capacitance: 1.11 microfarad** 190mm long

Steps of 0.001uF operating voltage 400V

**EM0931-001** 3 dial **Total capacitance: 11.1 microfarad** 190mm long

Steps of 0.01uF operating voltage 400V

**EM0932-001** 4 dial **Total capacitance: 11.11 microfarad** 240mm long

Steps of 0.001uF operating voltage 400V

Used to introduce an adjustable capacitance value into any electrical circuit.

Switching arrangement is 'Make before Break' so that as selection is made, the capacitance box cannot create an open circuit. Two terminals are fitted for the connection of either wires or 4mm banana plugs. A third terminal is provided for earthing or shielding of the housing.

**Designed and manufactured in Australia**

**INDUSTRIAL EQUIPMENT & CONTROL PTY. LTD.**  
 61-65 McClure St. Thornbury. 3071 Melbourne. Australia  
 Tel: 61 (0)3 9497 2555 Fax: 61 (0)3 9497 2166  
 e m 0 9 3 0 t o 0 9 3 2 - 0 0 1 . d o c 3 - J u n - 0 6